



GET MORE | GO FURTHER

SPECIFICATIONS SHEET

HAULMARK		HMVG46S	HMVG58S	HMVG510S	HMVG610S	HMVG612S	HMVG712T	HMVG712T	HMVG716T
<b>Body:</b>	Length	7'3"	9'6"	11'6"	11'10"	13'10"	14'1"	16'1"	18'1"
	Width	4'	5'	5'	6'	6'	6'9"	6'9"	6'9"
<b>Overall:</b>	Length	9'5"	11'4"	13'4"	14'7"	16'7"	16'7"	18'7"	20'7"
	Width	69"	81"	81"	93"	93"	102"	102"	102"
	Height	78"	84"	84"	90"	90"	91"	91"	91"
<b>Interior:</b>	Length	6'11"	9'2"	11'2"	11'6"	13'6"	13'8"	15'8"	17'8"
	Width	45"	57"	57"	69"	69"	78"	78"	78"
	Height	60"	66"	66"	72"	72"	72"	72"	72"
	Platform Height	18"	18"	18"	18"	18"	19"	19"	19"
<b>Axle:</b>	Quantity	Single	Single	Single	Single	Single	Tandem	Tandem	Tandem
	Capacity (lbs.)	2500	3500	3500	3500	3500	3500	3500	3500
	Type	4"Drop	4"Drop	4"Drop	4"Drop	4"Drop	4"Drop	4"Drop	4"Drop
	Suspension	Spring	Spring	Spring	Spring	Spring	Spring	Spring	Spring
	Brakes	Optional	Optional	Optional	Optional	Optional	Electric Drum	Electric Drum	Electric Drum
<b>Tire:</b>	Size	15"	15"	15"	15"	15"	15"	15"	15"
	Load Range	C	C	C	C	C	C	C	C
<b>Hitch:</b>	Ball Size	2"	2"	2"	2"	2"	2-5/16"	2-5/16"	2-5/16"
	To Top of Ball	16"	16"	16"	16"	16"	17"	17"	17"
<b>Hitch Weight (% of Curb Weight)</b>		10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%
<b>Weight</b>	Curb Weight (lbs.)	660	980	1080	1205	1325	1760	1860	1960
	GVWR (lbs.)	2500	2990	2990	2990	2990	7000	7000	7000
	Avg. Payload (lbs.)	1840	2010	1910	1785	1665	5240	5140	5040
	Style	Swing	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp	Ramp
<b>Rear Door:</b>	Width	40"	52"	52"	64"	64"	74"	74"	74"
	Height	54"	60"	60"	66"	66"	66"	66"	66"
	Lock Style	Bar Lock	Bar Locks	Bar Locks	Bar Locks	Bar Locks	Bar Locks	Bar Locks	Bar Locks
	Main Rails	2"x 3"	2"x 3"	2"x 3"	2"x 3"	2"x 3"	2"x4"	2"x4"	2"x4"
	12v End Connector	4-way	4-way	4-way	4-way	4-way	7-way	7-way	7-way
	DryMax® High Performance Floor	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"