



HSE-1002-0MG10

Pump: Direct triplex General pump with ceramic plungers · Stainless-steel and brass unloader valve · Forged brass manifold · Thermal relief valve

Motor: Totally enclosed fan-cooled electric motor with manual thermal overload protection · 35-foot power cord with in-line GFCI which meets required CSA certification · Solid state electronic ignition

Frame: Reinforced powder coated steel tube frame with center balanced lifting hook · Electric cord hanger · Powder coated steel gun/wand holder · Flat-free tires · Locking tire brake

Components: Energy-efficient top-fired heat exchanger designed for convenient troubleshooting and easy maintenance · High quality fuel filter/water separator ensures clean fuel supply · Complete system diagnostic board · Float tank · Pressure and high limit safety controls · No. 1 or No. 2 diesel or kerosene fired burner (Bio-fuel not approved at this time) · Polyethylene burner fuel tank · Easy coil drain helps prevent freezing in cold weather

Unit Includes: Quick connect nozzles (0°, 15°, 25° and 40°) · 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors · Professional-grade insulated trigger gun with safety lock-off · Adjustable pressure insulated dual lance

Miscellaneous: Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F · Water output temperature is 190°-200°F

Specifications

PSI 1000

GPM 2.0

HORSEPOWER/MOTOR 1.5 HP, 120V, 1Ø, 15.0A

PUMP General

PLUG TYPE NEMA 5-15P

BURNER FUEL TANK CAPACITY 4.0 gallon

BURNER FUEL CONS. 1.33 gph

BTU PER HOUR 186,000

Weights & Dimensions

NET WEIGHT 295 lbs.

SHIPPING WEIGHT 418 lbs.

LENGTH 43 in.

WIDTH 29.5 in.

HEIGHT 36.5 in.