



### *HSE-2003-0MG10*

**Pump:** Direct triplex General pump with ceramic plungers · Stainless-steel and brass unloader valve · Forged brass manifold · Thermal relief valve

**Motor:** Totally enclosed fan-cooled electric motor with manual thermal overload protection · 35-foot power cord with in-line GFCI which meets required CSA certification · Solid state electronic ignition

**Frame:** Reinforced powder coated steel tube frame with center balanced lifting hook · Electric cord hanger · Powder coated steel gun/wand holder · Flat-free tires · Locking tire brake

**Components:** Energy-efficient top-fired heat exchanger designed for convenient troubleshooting and easy maintenance · High quality fuel filter/water separator ensures clean fuel supply · Complete system diagnostic board · Float tank · Pressure and high limit safety controls · No. 1 or No. 2 diesel or kerosene fired burner (Bio-fuel not approved at this time) · Polyethylene burner fuel tank · Easy coil drain helps prevent freezing in cold weather

**Unit Includes:** Quick connect nozzles (0°, 15°, 25° and 40°) · 50-foot x 3/8-inch steel wire-braided pressure hose with swivel, quick connects and bend restrictors · Professional-grade insulated trigger gun with safety lock-off · Adjustable pressure insulated dual lance

**Miscellaneous:** Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F · Water output temperature is 190°-200°F

## Specifications

PSI 2000

GPM 2.8

HORSEPOWER/MOTOR 4.0 HP, 230V, 1Ø, 18.0A

PUMP General

PLUG TYPE NEMA 6-20P

BURNER FUEL TANK CAPACITY 4.0 gallon

BURNER FUEL CONS. 1.53 gph

BTU PER HOUR 214,000

## Weights & Dimensions

NET WEIGHT 316 lbs.

SHIPPING WEIGHT 439 lbs.

LENGTH 43 in.

WIDTH 29.5 in.

HEIGHT 36.5 in.