



HSE-3504-0M10

Pump: Belt drive triplex piston General pump with ceramic plungers · Stainless-steel and brass unloader valve · Forged brass manifold · Thermal relief valve · High pressure detergent injection

Motor: Totally enclosed fan-cooled electric motor with manual thermal overload protection · 35-foot power cord

Frame: Reinforced powder coated steel tube frame with center balanced lifting hook · Powder coated steel hose reel mounting bracket · Electric cord hanger · Powder coated steel gun/wand holder · Solid steel threaded axles · Pneumatic tires · Locking tire brake

Components: High quality fuel filter/water separator ensures clean fuel supply · Complete system diagnostic board · Float tank · Pressure and high limit safety controls · No. 1 or No. 2 diesel or kerosene

fired burner (Bio-fuel not approved at this time) · Polyethylene burner fuel tank · Easy coil drain helps prevent freezing in cold weather · Electrodes are self-gapping for proper ignition and combustion · Energy efficient top-fired powder coated heat exchanger designed for convenient trouble-shooting and easy maintenance · Heavy-duty dual cogged belt drive system to prevent slippage

Unit Includes: Quick connect nozzles (0°, 15°, 25° and 40°)· 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors · Professional-grade insulated trigger gun with safety lock-off · Adjustable pressure insulated dual lance

Miscellaneous: Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Specifications

PSI 3500

GPM 3.3

PUMP General

PLUG TYPE NEMA 6-50P

BURNER FUEL TANK CAPACITY 10.0

HORSEPOWER/MOTOR 10.0 HP, 230V, 1Ø, 39.0A

BURNER FUEL CONS. 2.10 gph

BTU PER HOUR 294,000

Weights & Dimensions

NET WEIGHT 631 lbs.

SHIPPING WEIGHT 761 lbs.

LENGTH 49.5 in.

WIDTH 28 in.

HEIGHT 40.5 in.