



HSP-2503-0MMH

Pump: Direct drive triplex piston Mi-T-M pump with ceramic plungers · Stainless-steel and brass unloader valve · Forged brass manifold · Thermal relief valve

Engine: Performance-proven Honda GX200 OHV engine with low-oil protection and recoil start

Frame: Reinforced powder coated steel tube frame with center balanced lifting hook · Wand holder · Solid steel threaded axles · Flat-free tires · Locking tire brake

Components: High quality fuel filter/water separator ensures clean fuel supply · Complete system diagnostic board · On/off burner switch · Pressure and high limit safety controls · No. 1 or No. 2 diesel or

kerosene fired burner (Bio-fuel not approved at this time) · Polyethylene burner fuel tank · Easy coil drain helps prevent freezing in cold weather · Energy efficient top fired powder coated heat exchanger designed for convenient troubleshooting and easy maintenance

Unit Includes: Quick connect nozzles (0, 15, 25 and 40-degree) · 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors · Professional-grade insulated trigger gun with safety lock-off · Adjustable pressure insulated dual lance

Miscellaneous: Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Specifications

PSI 2500

GPM 2.6

DISPLACEMENT/ENGINE 196cc Honda GX200 OHV

PUMP Mi-T-M

FUEL TANK CAPACITY 0.95-gallon

BURNER FUEL CAPACITY 4.0 gallon

BURNER FUEL CONS. 1.53 gph

BTU PER HOUR 210,000

Weights & Dimensions

NET WEIGHT 295 lbs.

SHIPPING WEIGHT 411 lbs.

LENGTH 43 in.

WIDTH 29.5 in.

HEIGHT 36.5 in.