



HSP-3003-3MGH

Pump: Direct drive triplex piston AR pump · Stainless-steel and brass unloader valve · Forged brass manifold · Thermal relief valve · Low pressure detergent injection · External bypass system allows more water into the system to protect from heat build-up

Engine: Performance-proven Honda GX270 OHV engine with low-oil protection and recoil start

Frame: Reinforced powder coated steel tube frame with center balanced lifting hook · Powder coated steel hose reel mounting bracket · Wand holder · Solid steel threaded axles · Flat-free tires · Locking tire brake

Components: High quality fuel filter/water separator ensures clean fuel supply · Complete system diagnostic board · Pressure and high limit safety controls · No. 1 or No. 2 diesel or kerosene fired burner (Bio-fuel not approved at this time) · Polyethylene burner fuel tank · Easy coil drain helps prevent freezing in cold weather · Patented Electro Magnetic Firing (EMF) System · Energy efficient top fired powder coated heat exchanger designed for convenient trouble-shooting and easy maintenance · On/off burner switch

Unit Includes: Quick connect nozzles (0°, 15°, 25° and 40°) · 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors · Professional-grade insulated trigger gun with safety lock-off · Adjustable pressure insulated dual lance

Miscellaneous: Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Specifications

PSI 3000

GPM 2.9

DISPLACEMENT/ENGINE 270cc Honda GX270 OHV

PUMP AR, external bypass

BURNER FUEL CAPACITY 5.5 gallon

FUEL TANK CAPACITY 1.59-gallons

BURNER FUEL CONS. 1.84 gph

BTU PER HOUR 253,000

Weights & Dimensions

NET WEIGHT 407 lbs.

SHIPPING WEIGHT 530 lbs.

LENGTH 43 in.

WIDTH 30 in.

HEIGHT 41 in.