



### *HSP-3504-3MGH*

**Pump:** Direct drive triplex piston AR pump · Stainless-steel and brass unloader valve · Forged brass manifold · Thermal relief valve · Low pressure detergent injection · External bypass system allows more water into the system to protect from heat build-up

**Engine:** Performance-proven Honda GX390 OHV engine with low-oil protection and recoil start

**Frame:** Reinforced powder coated steel tube frame with center balanced lifting hook · Powder coated steel hose reel mounting bracket · Wand holder · Solid steel threaded axles · Locking tire brake · Flat-free tires

**Components:** High quality fuel filter/water separator ensures clean fuel supply · Complete system diagnostic board · Pressure and high limit safety controls · No. 1 or No. 2 diesel or kerosene fired burner (Bio-fuel not approved at this time) · Polyethylene burner fuel tank · Easy coil drain helps prevent

freezing in cold weather · Patented Electro Magnetic Firing (EMF) System · Energy efficient top fired powder coated heat exchanger designed for convenient trouble-shooting and easy maintenance · On/off burner switch

**Unit Includes:** Quick connect nozzles (0°, 15°, 25° and 40°) · 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors · Professional-grade insulated trigger gun with safety lock-off · Adjustable pressure insulated dual lance

**Miscellaneous:** Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

### *Specifications*

PSI 3500

GPM 3.3

DISPLACEMENT/ENGINE 389cc Honda GX390 OHV

PUMP AR, external bypass

FUEL TANK CAPACITY 1.70-gallons

BURNER FUEL TANK CAPACITY 5.5 gallon

BURNER FUEL CONS. 2.14 gph

BTU PER HOUR 294,000

### *Weights & Dimensions*

NET WEIGHT 428 lbs.

SHIPPING WEIGHT 551 lbs.

LENGTH 43 in.

WIDTH 30 in.

HEIGHT 41 in.