



### *MH-0075-0M10*

**Frame:** Rugged steel body · Extension cord wrap · Powder coated hood and fuel tank

**Burner Head:** Clamped hoses · Secured photo cell · 1-piece cast aluminum · Secured fully insulated ignition connection

**Motor:** Heavy-duty, high quality cast aluminum enclosed electric motor

**Components:** Built-in temperature control thermostat with control dial · High performance fan · Power switch · Secured internal components · Integral overheat and flame-out safety · Fuel gauge · Integrated fuel pressure gauge · Oversized fuel cap · High limit temperature shut-off · Sure start ignition for cold temperature starts · Dual connector ignitor

**Factory tested for multiple fuels:** Kerosene, JP8/Jet A fuel, No. 1 or No. 2 fuel oil and No. 1 or No. 2 diesel fuel

**For use in workshops, garages, construction sites and farms with proper ventilation.**

*Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations, and/or ordinances.*

*Please see heater "Owner's Manual" included with each heater for a complete list of important safety information.*

**Important Notes:**

- Not for use in residential living areas or inadequately ventilated areas.
- Proper ventilation required during operation.
- Must be plugged into an approved standard electrical outlet for operation.

## Specifications

AIR PUMP PRESSURE 4.0 PSI

AC POWER 120 Volt/60Hz/1.5 Amp

MOTOR SIZE 1/8 HP

FUEL TANK CAPACITY 5.0 gallons

HEAT OUTPUT 75,000 BTU

HOT-AIR FLOW 240 CFM

FUEL COMSUMPTION 0.56 gal./hr.

MAX. OPERATING HOURS 8.9 hours

HEATING AREA 1700 sq. ft.

MULTI-FUEL CAPABLE Yes

## Weights & Dimensions

NET WEIGHT 28 lbs.

SHIPPING WEIGHT 33 lbs.

LENGTH 30 in.

WIDTH 13 in.

HEIGHT 15 in.