



### ***MH-0190-0M10***

**Frame:** Rugged steel body · Extension cord wrap · Powder coated hood and fuel tank · Powder coated steel handles for easy lifting · 10-inch pneumatic tires · Spare parts storage system (located on back of unit) · Fuel drain plug

**Burner Head:** Clamped hoses · Secured photo cell · 1-piece cast aluminum · Secured fully insulated ignition connection

**Motor:** Heavy-duty, high quality cast aluminum enclosed electric motor

**Components:** Built-in temperature control thermostat with control dial and digital temperature read-out · High performance fan · Power switch · Secured internal components · Integral overheat and flame-out safety · Fuel gauge · Integrated fuel pressure gauge · Oversized fuel cap · High limit temperature shut-off · Sure start ignition for cold temperature starts · Dual connector ignitor · Error indicator read-out

**Factory tested for multiple fuels:** Kerosene, JP8/Jet A fuel, No. 1 or No. 2 fuel oil and No. 1 or No. 2 diesel fuel

**For use in workshops, warehouses, garages, construction sites and farms with proper ventilation.**

*Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations, and/or ordinances.*

*Please see heater "Owner's Manual" included with each heater for a complete list of important safety information.*

**Important Notes:**

- Not for use in residential living areas or inadequately ventilated areas.
- Proper ventilation required during operation.
- Must be plugged into an approved standard electrical outlet for operation.

***Specifications***

HEAR OUTPUT 190,000 BTU

FUEL CONSUMPTION 1.42 gal./hr.

HOT-AIR FLOW 30 CFM

AIR PUMP PRESSURE 7.5 PSI

AC POWER 120 Volt/60Hz/2.7 Amp

MAX OPERATING HOURS 9.1 hours

MOTOR SIZE 1/4 HP

FUEL TANK CAPACITY 13.0 gallons

HEATING AREA 4,300 sq. ft.

MULTI-FUEL CAPABLE Yes

***Weights & Dimensions***

NET WEIGHT 58 lbs.

SHIPPING WEIGHT 65 lbs.

LENGTH 42 in.

WIDTH 24 in.

HEIGHT 26 in.