



MH-0215-0M10

Frame: Rugged steel body · Extension cord wrap · Powder coated hood and fuel tank · Powder coated steel handles for easy lifting · 10-inch pneumatic tires · Spare parts storage system (located on back of unit) · Fuel drain plug

Burner Head: Clamped hoses · Secured photo cell · 1-piece cast aluminum · Secured fully insulated ignition connection

Motor: Heavy-duty, high quality cast aluminum enclosed electric motor

Components: Built-in temperature control thermostat with control dial and digital temperature read-out · High performance fan · Power switch · Secured internal components · Integral overheat and flame-out safety · Fuel gauge · Integrated fuel pressure gauge · Oversized fuel cap · High limit temperature shut-off · Sure start ignition for cold temperature starts · Dual connector ignitor · Error indicator read-out

Factory tested for multiple fuels: Kerosene, JP8/Jet A fuel, No. 1 or No. 2 fuel oil and No. 1 or No. 2 diesel fuel

For use in workshops, garages, construction sites and farms with proper ventilation.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations, and/or ordinances.

Please see heater "Owner's Manual" included with each heater for a complete list of important safety information.

Important Notes:

- Not for use in residential living areas or inadequately ventilated areas.
- Proper ventilation required during operation.
- Must be plugged into an approved standard electrical outlet for operation.

Specifications

HOT-AIR FLOW 670 CFM
AIR PUMP PRESSURE 9.0 PSI
HEAT OUTPUT 215,000 BTU
AC POWER 120 Volt/60Hz/2.8 Amp
MOTOR SIZE 1/3 HP
FUEL TANK CAPACITY 13.0 gallons
FUEL CONSUMPTION 1.63 gal./hr.
MAX. OPERATING HOURS 8.0 hours
HEATING AREA 5,300 sq. ft.
MULTI-FUEL CAPABLE Yes

Weights & Dimensions

NET WEIGHT 61 lbs.
SHIPPING WEIGHT 68 lbs.
LENGTH 42 in.
WIDTH 24 in.
HEIGHT 26 in.